



NOTES:

MATERIAL:

- 1 HOUSING MATERIAL
- 2 CONTACT MATERIAL
- 3 PLATING
- ELECTRICAL:
- 1. VOLTAGE RATING
- 2. CURRENT RATING
- 3. CONTACT RESISTANCE
- 4. INSULATION RESISTANCE
- 5. DIELECTRIC WITHSTANDING RESISTANCE

MECHANICAL:

- 1 DURRABILITY
- 2 PCB RETENTION PRE-SOLDER

ENVIRONMENTAL:

- 1. STORAGE
- 2. OPERATION

:125 VAC RMS

:15 AMP.

:30 MILLIONHMS MAX.

:500 MEGOHMS MIN @ 500V DC.

:1000V AC RMS 50HZ MIN.

:750 CYCLES MIN

:1 LB MIN.

: -40°~+95°

: 0? TO 70?.

PC Board Layout

Component Side Shown

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	TITLE:
CHECKED:	DATE:	RJ45-8P/8C 1*2 TAB-Down H=20.57 全塑 弯插
DRAWN:	DATE:	CLIENT P/N
SXA	2019-06-21	R-RJ45R08P-A201
		UNIT
		mm
		SCALE
		free
		REV.
		A
		HY04

深圳市灿科盟实业有限公司
CHANKEMENG INDUSTRY CO., LTD