



NOTES:

MATERIAL :

- 1.HOUSING MATERIAL :GLASS FILLED POLYESTER U94V-0.
- 2.CONTACT MATERIAL :PHOSPHOR BRONZE φ0.45mm.
- 3.PLATING :GOLD PLATING OVER NICKEL.
- 4.SHIELD :0.20mm THICKNESS COPPER ALLOY WITH NICKEL PLATED.

ELECTRICAL:

- 1.VOLTAGE RATING :125 VAC RMS.
- 2.CURRENT RATING :15 AMP.
- 3.CONTACT RESISTANCE :30 MILLIOHMS MAX.
- 4.INSULATION RESISTANCE :500 MEGOHMS MIN @ 50V DC.
- 5.DIELECTRIC WITHSTANDING :1000V AC RMS 50HZ 1MIN.

MECHANICAL:

- 1.DURABILITY :750 CYCLES MIN.
- 2.PCB RETENTION PRE-SOLDER:1LB MIN.

ENVIRONMENTAL:

- 1.STORAGE :-40°~+85°
- 2.OPERATION :0° TO 70°

TOLERANCE TABLE	
	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	<b>C</b> 深圳市灿科盟实业有限公司 kmtw CHANKLEMENT INDUSTRYCO., LTD
CHECKED:	DATE:	
DRAWN:	DATE:	TITLE: R145-8P/8C TAB-Down H=21.2 弯插 带屏蔽 无灯 无弹 脚后3.05
ZYJ	2017-02-19	PART. NO. R-RJ45R08P-B005 UNIT mm SCALE Free FILE NO. Ckmtw-RJ45-0178 REV. A HY04